

Dual Purpose Suction and Delivery Hose – 3mm Liner



Recommended for	Agricultural, industrial and mining applications where hardwall hose is required to function in either suction or pressure applications.	
Temperature range	-20°C to +80°C	
Construction	Liner	NR compound
	Reinforcement	Wire helix embedded between plies of high-strength synthetic fabric
	Cover	NR/SBR compound; weather and abrasion resistant
Hose ends	Plain, cuffed or with built-in couplings	
Lengths	All IDs: (alternate lengths available on request up to 20m) ≥ 450mm maximum up to 10m	

Theoretical technical information					
Hose ID (mm)		Approx. OD (mm)	Rated WP (bar)	Suction (bar)	Min. Bend Radius (mm)
Nom.	Act.				
50	50.8	78	10	0.9	312
60	63.0	90	10	0.9	360
75	76.3	103	10	0.9	412
100	101.6	128	10	0.9	512
125	127.0	154	10	0.9	616
150	152.4	180	10	0.9	720
200	203.2	235	10	0.9	940
250	254.0	286	10	0.9	1716
300	304.8	339	7	0.9	2034
350	355.6	390	7	0.9	2340
400	406.4	444	7	0.9	2664
450	457.2	496	7	0.9	2976

* Disclaimer: Information offered as a guide and is subject to change without notice.