

## Dual Purpose Suction and Delivery Hose – 6mm Liner



3

<b>Recommended for</b>	Agricultural, industrial and mining applications where hardwall hose is required to function in either suction or pressure applications.	
<b>Temperature range</b>	-20°C to +80°C	
<b>Construction</b>	<b>Liner</b>	NR compound
	<b>Reinforcement</b>	Wire helix embedded between plies of synthetic fabric
	<b>Cover</b>	NR/SBR compound; weather and abrasion resistant
<b>Hose ends</b>	Plain, cuffed or with built-in couplings	
<b>Lengths</b>	All IDs: (alternate lengths available on request up to 20m) ≥ 450mm maximum up to 10m	

Theoretical technical information					
Hose ID (mm)		Approx. OD (mm)	Rated WP (bar)	Suction (bar)	Min. Bend Radius (mm)
Nom.	Act.				
50	50.8	84	10	0.9	336
60	63.0	96	10	0.9	384
75	76.3	109	10	0.9	436
100	101.6	134	10	0.9	536
125	127.0	160	10	0.9	640
150	152.4	185	10	0.9	740
200	203.2	241	10	0.9	964
250	254.0	294	10	0.9	1764
300	304.8	345	7	0.9	2070
350	355.6	396	7	0.9	2376
400	406.4	451	7	0.9	2706
450	457.2	501	7	0.9	3006