

## Dual Purpose Suction and Delivery Hose – 9mm Liner



<b>Recommended for</b>	Agricultural, industrial and mining applications where hardwall hose is required to function in either suction or pressure applications.	
<b>Temperature range</b>	-20°C to +80°C	
<b>Construction</b>	<b>Liner</b>	NR compound
	<b>Reinforcement</b>	Wire helix embedded between plies of high-strength synthetic fabric
	<b>Cover</b>	NR/SBR compound; weather and abrasion resistant
<b>Hose ends</b>	Plain, cuffed or with built-in couplings	
<b>Lengths</b>	All IDs: (alternate lengths available on request up to 20m) ≥ 450mm maximum up to 10m	

Theoretical technical information					
Hose ID (mm)		Approx. OD (mm)	Rated WP (bar)	Suction (bar)	Min. Bend Radius (mm)
Nom.	Act.				
50	50.8	89	10	0.9	356
60	63.0	102	10	0.9	408
75	76.3	115	10	0.9	460
100	101.6	140	10	0.9	560
125	127.0	166	10	0.9	664
150	152.4	191	10	0.9	764
200	203.2	250	10	0.9	1000
250	254.0	300	10	0.9	1800
300	304.8	351	7	0.9	2106
350	355.6	402	7	0.9	2412
400	406.4	457	7	0.9	2742
450	457.2	508	7	0.9	3048