

2PW PowerWash



-Size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	Kg/100m	REF.
-5	8	5/16	0.61	15.6	5800	40.0	17400	120.0	80	34	2PW05
-6	10	3/8	0.69	17.5	5800	40.0	17400	120.0	90	41	2PW06
-5	8	5/16	0.61	15.6	5800	40.0	17400	120.0	80	34	2PW05B
-6	10	3/8	0.69	17.5	5800	40.0	17400	120.0	90	41	2PW06B
-8	12	1/2	0.81	20.6	5800	40.0	15225	105.0	125	51	2PW08B
-6	10	3/8	0.69	17.5	5800	40.0	17400	120.0	90	41	2PW06G

Recommended for	Use on hot and cold water high-pressure cleaning equipment where heavy-duty service is required. Suited for agricultural, sports, valet and maintenance service applications. Grey and blue PowerWash are suitable for use in hospitals, swimming pools and other applications where hygiene is of the utmost importance. Not recommended for steam service.
Tube	Black. NBR (Nitrile) based
Reinforcement	Two-wire braid
Cover	Blue (NBR/PVC based); grey (NBR/PVC based); black (CR based)
Temperature range	-40°C to +155°C
Standards	Gates proprietary
Couplings	MegaCrimp®

