

1PW PowerWash



-Size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	Kg/100m	REF.	
-4	6	1/4	0.53	13.5	2900	20.0	13100	90.0	70	22	1PW04	
-5	8	5/16	0.59	15.0	2900	20.0	12325	85.0	80	26	1PW05	
-6	10	3/8	0.69	17.4	2900	20.0	10440	72.0	90	35	1PW06	
-5	8	5/16	0.59	15.0	2900	20.0	12325	85.0	80	26	1PW05B	
-6	10	3/8	0.69	17.4	2900	20.0	10440	72.0	90	35	1PW06B	
-8	12	1/2	0.81	20.6	2900	20.0	9280	64.0	125	43	1PW08B	
-6	10	3/8	0.69	17.4	2900	20.0	10440	72.0	90	35	1PW06G	
-8	12	1/2	0.81	20.6	2900	20.0	9280	64.0	125	43	1PW08G	

Recommended for	Use on hot and cold water high-pressure cleaning equipment where heavy-duty service is required. Suited for agricultural, sports, valet and maintenance service applications. Grey and blue PowerWash are suitable for use in hospitals, swimming pools and other applications where hygiene is of the utmost importance. Not recommended for steam service.
Tube	Black; NBR (Nitrile) based
Reinforcement	One-wire braid
Cover	Blue (NBR/PVC based); grey (NBR/PVC based); black (CR based)
Temperature range	-40°C to +155°C
Standards	Gates proprietary
Couplings	MegaCrimp®
	B = Blue G = Grey

