

TWFB1 and TAWFB1 – Smoothflex



Description	TWFB1 SMOOTHFLEX smooth bore flexible Teflon® hose with stainless steel helix and high-tensile stainless steel braid
Construction	Low profile helically convoluted PTFE (polytetrafluorethylene) liner with stainless steel helix and a AISI 304 high-tensile, stainless steel braid; the hose has a very good vacuum and kink resistance
Fittings	Hose fittings with hydraulic tail Hose assembling without de-convoluting the inner liner -specially designed for hydraulic tail fittings

Specifications									
	D1	D2	D3	R	WP	BP	Weight	REF	REF
Size	min.	min.	min.	mm	Bar 20°C		gr/m	VIRGIN	Anti-static
1/2"	11.50	1.25	17.80	38	50	250	290	TWFB1012	TAWFB1012
5/8"	15.50	1.25	21.80	42	50	250	361	TWFB1016	TAWFB1016
3/4"	20.00	1.5	26.70	50	60	290	430	TWFB1020	TAWFB1020
1"	22.80	1.5	29.80	70	40	210	653	TWFB1025	TAWFB1025
1 1/4"	30.50	1.5	37.50	85	45	210	750	TWFB1032	TAWFB1032
1 1/2"	36.50	2	46.50	100	40	175	800	TWFB1040	TAWFB1040
2"	48.50	2	58.30	140	25	135	950	TWFB1050	TAWFB1050