

PH301 – Sewer Jet 2500 PSI



Application	Standard sewer cleaning vehicles and cleaning equipment. Special construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and subject to increased lifetime.	
Applicable Standard	Proprietary product	
Construction	Core	Thermoplastic elastomer
	Reinforcement	1 or 2 braids of synthetic fibre
	Cover	Orange colour – polyurethane
Temperature Range	-40°C to + 60°C	

Part No.	Dash Size	DN	Hose ID (Nom.)		Hose OD (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			Inch	mm.	Inch	mm.	PSI	Bar	PSI	Bar	Inch	mm.
PH301-3	-3	5	3/16	4.8	0.405	10.3	2500	175	6250	438	40	1.6
PH301-4	-4	6	1/4	6.4	0.490	12.4	2500	175	6250	438	40	1.6
PH301-8	-8	12	1/2	12.8	0.810	20.6	2500	175	6250	438	100	4.0
PH301-12	-12	20	3/4	19.2	1.150	29.2	2500	175	6250	438	125	5.0
PH301-16	-16	25	1	25.5	1.450	36.8	2500	175	6250	438	160	6.4
PH301-20	-20	32	1.1/4	32.0	1.800	45.7	2500	175	6250	438	250	10.0