

PH302 – Sewer Jet 3000 PSI



Application	Standard sewer cleaning vehicles and cleaning equipment. Special construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover, resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and subject to increased lifetime.	
Applicable Standard	Proprietary product	
Construction	Core	Thermoplastic elastomer
	Reinforcement	1 or 2 braids of synthetic fibre plus one special extra braid
	Cover	Blue colour – polyurethane
Temperature Range	-40°C to +60°C	

Part No.	Dash Size	DN	Hose ID (Nom.)		Hose OD (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			Inch	mm.	Inch	mm.	PSI	Bar	PSI	Bar	Inch	mm.
PH302-6	-6	10	3/8	9.6	0.650	16.5	3000	210	7500	525	75	3.0
PH302-8	-8	12	1/2	12.8	0.880	22.4	3000	210	7500	525	100	4.0
PH302-12	-12	20	3/4	19.2	1.250	31.8	3000	210	7500	525	125	5.0
PH302-16	-16	25	1	25.5	1.525	38.7	3000	210	7500	525	160	6.4
PH302-20	-20	32	1.1/4	32.0	1.840	46.7	3000	210	7500	525	250	10.0