

PH303 – Sewer Jet 4000 PSI



Application	Standard sewer cleaning vehicles and cleaning equipment. Special construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover, resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and subject to increased lifetime.	
Applicable Standard	Proprietary product	
Construction	Core	Thermoplastic elastomer
	Reinforcement	1 or 2 braids of synthetic fibre / Aramid fibre plus one special synthetic fibre braid
	Cover	Green colour – polyurethane
Temperature Range	-40°C to + 60°C	

Part No.	Dash Size	DN	Hose ID (Nom.)		Hose OD (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			Inch	mm.	Inch	mm.	PSI	Bar	PSI	Bar	Inch	mm.
PH303-3	-3	5	3/16	4.8	0.405	10.3	4000	280	12000	840	40	1.6
PH303-4	-4	6	1/4	6.4	0.500	12.7	4000	280	12000	840	40	1.6
PH303-6	-5	10	3/8	9.6	0.670	17.0	4000	280	12000	840	75	3.0
PH303-8	-8	12	1/2	12.8	0.920	23.4	4000	280	12000	840	75	3.0
PH304-8	-8	12	1/2	12.8	0.800	20.3	4000	280	16000	1120	100	4.0
PH303-12	-12	20	3/4	19.2	1.150	29.2	3600	250	9000	625	125	5.0
PH303-16	-16	25	1	25.5	1.500	37.9	3600	250	9000	625	160	6.4
PH303-20	-20	32	1.1/4	32.0	1.800	45.7	3600	250	9000	625	250	10.0