

PH326 – Beverage Dispensing



Application	High pressure beverage dispensing lines 210 to 420 PSI. Specifically designed for gases and gas mixtures used in fixed and mobile beverage dispensing units. Special flavour free tube material eliminates contamination and conforms to FDA and EC regulations.	
Applicable Standard	Proprietary product	
Construction	Core	Thermoplastic elastomer, food quality and FDA approved
	Reinforcement	PH326 single or double braid of synthetic fibre, PH327 single steel braid, PH328 single braid of aramid fibre
	Cover	Black colour – polyurethane, pin pricked
Temperature Range	-40°C to + 80°C	

Part No.	Dash Size	DN	Hose ID (Nom.)		Hose OD (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			Inch	mm.	Inch	mm.	PSI	Bar	PSI	Bar	Inch	mm.
PH326-4	-4	6	1/4	6.4	0.480	12.2	3000	210	12000	840	35	1.4
PH327-3	-3	5	3/16	4.8	0.380	9.7	5000	350	20000	1400	40	1.6
PH327-4	-4	6	1/4	6.4	0.460	11.7	4650	320	18600	1280	45	1.8
PH328-2	-2	3	1/8	3.2	0.320	8.1	6000	420	24000	1680	25	1.0
PH328-3	-3	5	3/16	4.8	0.405	10.3	5000	350	20000	1400	25	1.0
PH328-4	-4	6	1/4	6.4	0.490	12.4	5000	350	20000	1400	32	1.3