

PH343 – Paint Spray 2 WB



Application	High pressure airless paint spray system for 160 to 450 PSI. Suitable for applications requiring chemical resistance to solvents and aggressive fluids due to low permeation value of Polyamide. Also suitable for industrial gases.	
Applicable Standard	Proprietary product	
Construction	Core	Polyamide
	Reinforcement	Double steel wire braid
	Cover	Blue colour – polyurethane, pin pricked (optional). Available in twin and multi lines with different hose combination and size.
Temperature Range	-40°C to + 100°C. Temperature not to exceed +70°C for air and water based fluids.	

Part No.	Dash Size	DN	Hose ID (Nom.)		Hose OD (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
			Inch	mm.	Inch	mm.	PSI	Bar	PSI	Bar	Inch	mm.
PH343-4	-4	6	1/4	6.4	0.540	13.7	6500	450	26000	1800	100	4.0
PH343-5	-5	8	5/16	8.0	0.600	15.2	5800	400	23200	1600	110	4.4
PH343-6	-6	10	3/8	9.6	0.690	17.5	5500	380	22000	1520	127	5.1
PH343-8	-8	12	1/2	12.8	0.830	21.1	4350	300	17400	1200	178	7.1
PH343-12	-12	20	3/4	19.2	1.125	28.6	2300	160	9200	640	250	10.0