

High Pressure Jetting Hose

2 Series



Application	Heat exchanger tube cleaning (lancing) 2 series	
Temperature range	30 to +60°C	
Construction	Liner	POM
	Reinforcement	Two layers high-tensile wire spirals
	Cover	PA (colour: green)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
3.4	6.9	1000	14500	2500	36250	0.072
4.0	8.0	1200	17400	3000	43500	0.110
5.0	9.4	1040	15000	2600	37700	0.125
6.3	11.5	1000	14500	2500	36250	0.175

2k Series



Application	Hydraulic (industrial/hydro-test 10k) 2k series	
Temperature range	-30 to +60°C	
Construction	Liner	PA
	Reinforcement	Two layers high-tensile steel wire spirals /one layer high-tensile steel braid
	Cover	PUR (colour: black)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.0	9.8	1200	17400	3000	43500	0.185
6.2	12.9	1120	16240	2800	40600	0.300
8.0	14.5	88	12760	2200	31900	0.360

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
12.8	22.3	800	11600	2000	29000	0.690
18.8	28.2	560	8120	1400	20300	1.050
23.6	32.6	480	6960	1200	17400	1.200

2w Series



Application	High pressure hydraulic (tools/hydro-test 15k) 2w series	
Temperature range	-30 to +60°C	
Construction	Liner	PA
	Reinforcement	Four layers of high-tensile steel wire
	Cover	PUR (colour: black)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.0	9.8	1400	20300	3500	50750	0.160
6.0	12.0	1280	18560	3200	46400	0.230
8.0	14.3	1040	15000	2600	37500	0.314
10.0	17.2	1000	14500	2500	36250	0.430
12.8	20.8	1040	15000	2600	37700	0.620