

2wl Series



Application	High pressure hydraulic (ultra-flexible/hydro-test 15k) 2wl series	
Temperature range	-30 to +60°C	
Construction	Liner	PA
	Reinforcement	Four layers of high-tensile steel wire
	Cover	PUR (colour: black)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
5.9	12.0	1200	17400	3000	43500	0.237
8.0	14.0	1000	14500	2500	36250	0.317

4 Series



Application	Water jetting (hydro-test 15-25k) 4 series	
Temperature range	-30 to +60°C	
Construction	Liner	PA
	Reinforcement	Four layers high-tensile steel wire spirals
	Cover	PA (colour: grey)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.0	10.3	2160	31320	5400	78300	0.230
5.0	11.2	1800	26100	4500	65250	0.260
6.3	12.6	1500	21750	3800	55100	0.295
8.0	14.6	1500	21750	3800	55100	0.390
9.9	18.4	1500	21750	3800	55100	0.690
12.8	21.4	1280	18560	3200	46400	0.800
18.8	28.8	1040	15080	2600	37700	1.350