

4h and 4ht Series



Application	Water jetting (hydro-test 20k) 4h & 4ht series	
Temperature range	-30 to +60°C (*HHT -20 to +150°C)	
Construction	Liner	PA (*HHT has PVDF liner)
	Reinforcement	Four layers high-tensile steel wire spirals
	Cover	PA (colour: grey)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
12.8	22.0	1400	20300	3500	50760	0.880
12.8	22.0	1040	15000	3500	50760	1.000

6 Series



Application	Jetting/Cutting (Hydro-test 20-40k) 6 Series	
Temperature range	-30 to +60°C	
Construction	Liner	PUR
	Reinforcement	Six layers high-tensile steel wire spirals
	Cover	PA (Colour: Blue)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.0	11.5	2800	2800	7000	101500	0.365
4.8	13.2	2500	2500	6250	96250	0.450
8.0	16.4	2100	2100	5250	76150	0.640
12.8	23.4	1800	1800	4500	65250	1.160
18.8	32.8	1400	1400	3500	50760	2.170