

6h Series



Application	Jetting/Cutting (hydro-test 35-40k) 6h Series	
Temperature range	-30 to +60°C	
Construction	Liner	POM
	Reinforcement	Six layers high-tensile steel wire spirals
	Cover	PA (Colour: Red)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.6	14.4	2800	40600	7000	101527	0.563
4.6	14.4	2800	40600	7000	101527	0.563
7.7	18.8	2500	36250	6250	90650	0.925
7.7	18.8	2500	36250	6250	90650	0.925

8, 8h and 8uhp Series



Recommended for	Extremely high pressure jetting (hydro-test 40k) 8, 8h and 8uhp series	
Temperature range	-30 to +60°C	
Construction	Liner	POM
	Reinforcement	Eight layers high-tensile steel wire spirals
	Cover	PA (colour: purple/yellow for uhp)

Specifications						
ID (mm)	OD (mm)	Working pressure		Burst Pressure		Weight Kg/m
		Bar	PSI	Bar	PSI	
4.0	12.8	3200	46400	8000	116000	0.580
7.6	20.8	2800	40600	7000	101500	1.120
4.5	15.3	3200	46400	8000	116000	0.693
7.6	22.0	3200	46400	7400	107300	1.500